


Aru 78 Classic IN

Inwards opening tilt and turn wooden window

- Made to Measure Sizes
- Good thermal performance (Window Uw 0,96 W/m²K of window 1230x1480 mm; glass Ug-0,72)
- Frame and sash profile thickness 78 mm
- Timber selection:
 - fingerjointed or selected laminated pine timber;
 - laminated oak timber
- Timber finishing with waterbased paint or stain. Paint according to RAL colour chart, stain according to manufacturer's samples.
- Glazing with glazing beads inside, fastened with hidden nails, sealed with silicone in and out
- Glazing bar options:

 - penetrating bars
 glued on both sides of the glass+slats inside the glazing (Norwegian style)
 3. glued on both sides of the glass (Georgian style)

 - 4. dekorative bars inside the glazing





- special glasses (toughened, laminated, sun protection, self cleaning, pattern etc.), various glass spacers
 - tilt first opening (open in the turn position after unlocking)
- additional security elements of hardware key lockable handles, design handles
- fly net;
- jamb extensions, window boards;
- trickle vents
- Triangular windows




The bottom frame is protected with alumiinium profile

Openable window






Section without mullion Secondary sash/Primary sash



Section through fixed mullion Opening sash/Opening sash



Section through mullion Fixed light / Opening sash

OPENING Outside view



FIXED (direct glazing)



Tilt and turn (left/right) Min max L= 410...1710 mm max weight of sash 130 kg

H= 410...2720 mm.




Turn only (left/right) Min max L= 410...1710 mm H= 410...2720 mm, max weight of sash 130 kg



Min max L= 435...2510 mm H= 380...1329 mm, max weight of sash 80 kg

Handle positions:

60 Fixed window



- K Tilt position (ventilation)
- M Microventilation
- D Turn position for quick air exchange or window washing
- S Closed

NB! Minimum maximum dimensions and opening options also depend on the height and width ratio of the window and other factors. More information from our specialists. Manufacturer has reserved the right to make changes.