


AruAL 60 Classic EX AruAL 60 Modern EX

Outwards opening Scandinavian type wooden-aluminium windows

- Made to Measure Sizes
- Thermal performance of window Uw 1,3 W/m²K (openable window 1230x1480 mm; glass Ug-1,1)
- Frame 115 mm (or 95 mm) +aluminium cladding (127,5/107,5 mm)
- Sash profile thickness 60 mm+aluminium cladding
- Timber selection: laminated pine timber, laminated oak timber
- Timber finishing with waterbased paint or stain. Paint according to RAL colour chart, stain according to manufacturer's samples.
- Aluminium finishing according to RAL colour chart
- 1 sash gasket
- Double glazing thickness 26 mm
- Glazing sealed with internal and external gasket
- Glazing bar options:
 - 1. penetrating bars
 - 2. glued on both sides of glass+slats inside the glazing (Norwegian style)
 3. glued on both sides of glass (Georgian style)
 4. decorative bars inside the glazing



- Extras:
 - jamb extensions;
 - grooves for the extension (10x10 mm grooved frame);
 - window boards;
 - vents;
 - special glasses (toughened, laminated, sun protection, self cleaning, pattern etc.);
 - varios glass spacers;

 - key lockable handles, design handles;
- Different combinations of openable and fixed parts are possible in the common frame
- Triangular fixed windows Outside view



FIXED (direct glazing) Min sizes 330 x 330 mm



TOPGUIDED

Min max L= 370...1600 mm H= 370...1600 mm, sash weight max 60 kg



TOPSWING

Min max L= 380...1600 mm H= 595...1645 mm, sash weight max 60 kg





SIDEHUNG (left/right)


Min max L= 450...980 mm H= 515...2110 mm, sash weight max 40 kg



SIDE-SLIDEHUNG (concealed hinges; left/right)
Min max L= 395...1105 mm H= 515...1805 mm, sash weight max 50 kg








Openable window

Fixed window









Openable+openable

Openable+Fixed


Fixed+Fixed





Frame with extension





Grooved frame